

# BRAKE CABLE

Stranded bare or tinned copper conductors.  
105°C, 50 Volts.



## APPLICATIONS

For use as a general purpose low tension primary wire in automotive circuits where more than one conductor, color coding and flat configuration are required.

## CONSTRUCTION

Southwire's Brake Cable is manufactured using stranded bare or tinned copper conductors with individual PVC insulation and chemically bonded in parallel.

# Brake Cable

NO. OF CONDS.	SIZE AWG	NO. OF STRANDS	INSUL. THICKNESS		NOMINAL O.D.		NET WEIGHT	
			(mm)	(in.)	(mm)	(in.)	(kg/km)	(lbs/Mft)
2	18	16	.41	.016	6.02	.237	41.17	27.67
4	18	16	.41	.016	9.45	.372	51.37	34.52
2	16	19	.81	.032	7.98	.314	61.49	41.32
3	16	19	.58	.023	9.65	.38	69.27	46.56
4	16	19	.58	.023	13.34	.525	92.98	62.48
3	14	19	.58	.023	10.67	.42	99.64	66.96
2	12	19	.66	.026	8.81	.347	94.79	63.7
3	12	19	.69	.027	12.95	.51	152.56	102.53
2	14.2	19	.58	.023	7.7	.303	70.97	47.69
4	14.2	19	.58	.023	12.09	.476	94.24	63.34