

Triplex PowerGlide 600V Secondary UD

Aluminum Conductor.
Cross-linked Polyethylene (XLP) Insulation.
Easy to Pull or Push.



APPLICATIONS

- Used for secondary distribution and underground service at 600 volts or less.
- Designed for push-in or pull-in installation.
- Rated 90°C continuous operation, 130°C emergency overload and short-circuit 250°C.

SPECIFICATIONS

PowerGlide 600 volt secondary UD cable meets or exceeds the following applicable ASTM specifications:

- B-231 Aluminum 1350 Conductors, Concentric-Lay-Stranded.
- B-609 Aluminum 1350 Round Wire, Annealed and Intermediate Tempers, for Electrical Purposes.
- B-786 19 Wire Combination Unilay-Stranded Aluminum Conductors for Subsequent Insulation.
- B-901 Compressed Round Stranded Aluminum Conductors Using Single Input Wire.

PowerGlide 600 volt secondary UD cable insulation meets or exceeds all grade and type requirements of ANSI/ICEA S-105-692 and UL Standard 854 for Type USE-2.

CONSTRUCTION

Conductors are stranded, compressed 1350-H16/H26 aluminum, insulated with a cross-linked polyethylene meeting the requirements of ANSI/ICEA S-105-692. Two phase conductors and one neutral conductors are cabled to produce a twisted-conductor cable configuration. Twisted conductors are bound with an engineered spiral-wrapped glide wire that reduces installation friction and maintains bundle integrity. Neutral is identified with three yellow extruded stripes (YES) and has sequential footage markers. Conductors are durably surface printed for identification. Also available in sizes 250 kcmil through 500 kcmil with reduced 80 mils insulation thickness per ICEA and UL. Duplex and quadruplex configurations are also available in most common sizes.

PowerGlide Triplex 600V

Phase Conductors			Neutral Conductor			Diameter (mils)			Weight Per 1000 feet (lbs.)	Allowable Ampacities+	
Size (AWG or kcmil)	Strand-ing	Insul. Thick. (mils)	Size (AWG or kcmil)	Strand-ing	Insul. Thick. (mils)	Single Phase Cond.	Neutral Cond.	Complete Cable		Direct Burial	In Ducts
1/0	9	80	2	7	60	512	403	1236	394	215	160
2/0	11	80	1	9	80	555	473	1329	486	245	180
3/0	17	80	1/0	9	80	603	512	1432	589	280	205
3/0	17	80	3/0	17	80	603	603	1432	659	280	205
4/0	18	80	2/0	11	80	658	555	1551	717	315	240
4/0	18	80	4/0	18	80	658	658	1551	804	315	240
250	26	95	3/0	17	80	732	603	1711	861	345	265
350	37	95	4/0	18	80	831	658	1925	1126	415	320
500	37	95	350	37	95	980	831	2247	1608	495	395
750	61	110	500	37	95	1188	980	2696	2325	620	495

+ Ampacity: 90°C conductor temperature, 20°C ambient temperature, RHO factor 90, 100% load factor for three conductor triplex with neutral carrying only unbalanced load.